

OPTOELECTRONIC INSTRUMENTS AND SYSTEMS FOR GEOMETRIC QUANTITIES MEASUREMENT

PRODUCT CATALOG

2024

| | DISPLACEMENT AND POSITION MEASUREMENT | ¥ • | GAP MEASUREMENT |
|-------------|---|-----------|------------------------|
| → <u></u> ← | THICKNESS AND WIDTH MEASUREMENT | | PROFILE MEASUREMENT |
| → ↑ ↑ | OUTER DIAMETER AND PROFILE MEASUREMENT | ↓↓↓ | LEVEL MEASUREMENT |
| | INNER DIAMETER AND PROFILE MEASUREMENT | 2D | 2D MEASUREMENT |
| | VIBRATION AND RUN-OUT MEASUREMENT | 3D | 3D MEASUREMENT |
| | STRAIGHTNESS AND FLATNESS MEASUREMENT | | MACHINE VISION SYSTEMS |

ISO 9001-2015



Company «RIFTEK» was founded in 1993. The enterprise specializes in development and fabrication of optoelectronic instruments for measuring of geometrical quantities.

The basic product line includes:

- laser triangulation position sensors;
- 2D and 3D laser scanners;
- absolute linear encoders;
- optical micrometers;
- hardware and software system for welding robots;
- specialized systems for measuring dimensions, displacements and distances, thickness, diameter, etc.;
- measurement instruments for railway transport;
- machine vision systems.

RIFTEK products are delivered in more than 70 countries. Company representative offices operate in 45 countries.

RIFTEK company is certified according to ISO 9001:2015 in the field of management of quality of design and manufacture of optoelectronic instrumentation.

We offer integrated solution to control and automation problems — from sensing devices to multifunctional measuring and control systems.



GIUA-0038-QC

PURPOSE

Contactless dimensions, surface profile, deformation, vibration measurement, sorting, sensing presence or absence, positional checking, bulk materials and liquids level measurement.

OPERATION

Sensor operation is based on the principle of optical triangulation.

Radiation of a semiconductor laser is focused by an objective on an object. The radiation scattered at the object is collected on the CMOS array by the input lens. Object motion causes a corresponding motion of the image. Built-in signal processor calculates the distance to the object according to the light spot image position on the CMOS array.



MAIN FEATURES

- Measuring ranges from 2 to 2500 mm
- ±1 μm accuracy
- Sampling rate up to 70 kHz
- RS232/RS485/Ethernet/CAN/ CANopen +4...20 mA/0...10V/ModbusRTU
- Binocular sensors for laser scanning
- Binary and ASCII data formats
- Sensors with BLUE lasers to control high temperature, mirrored and semitransparent objects
- Sensors with IR lasers
- Mutual synchronization of the sensors (master-slave) for multi-axis measurement tasks
- Service Software for parameter setting and results visualization
- Free SDK and examples for Windows, Linux, .NET, MATLAB, LabVIEW

MODELS

RF603 — universal sensors

RF603HS — high speed sensors

RF600 / **RF600HS** — sensors with increased base distance and large measurement range. High speed sensors

RF602 — super compact sensors

RF607 — high-precision high-speed sensors

RF609 / RF609Rt / RF609Wi-Fi — laser probes for inner surface control



| | PARAMETER | | VALUE | | | | |
|-----------------------|---------------------------|-----------------------------|--|--|--|--|--|
| Output | digital | | RS232 (max. 460.8 kbit/s) or RS485 (max. 921.6 kbit/s) or RS232 and CAN V2.0B (max 1Mbit/s) or Ethernet and (RS32 or RS485) | | | | |
| Interface | | analog | 420 mA (≤500 Ω load) or 010 V | | | | |
| Synchronization input | | | 2.4 – 5 V (CMOS, TTL) | | | | |
| Logic output | | | programmed functions, NPN: 100 mA max; 40 V max for output | | | | |
| Power supply, V | | | 936 | | | | |
| Power consumption, W | | | 1.52 | | | | |
| Enclosure rating | | ng | IP67 (for the sensors with cable connector only) | | | | |
| | Vibration | | 20g/101000Hz, 6 hours, for each of XYZ axes | | | | |
| ent | Shock | | 30 g / 6 ms | | | | |
| ironm | Operation temperature, °C | | -10+60, (-30+60 for the sensors with built-in heater), (-30+120 for the sensors with built-in heater and air cooling housing) | | | | |
| Env | Permissible an | nbient light, lx | >30000 | | | | |
| | Relative humic | dity | 5-95% (no condensation) | | | | |
| | Storage tempe | rage temperature, °C -20+70 | | | | | |
| Housing | material | | aluminum | | | | |

UNIVERSAL LASER SENSORS

RF603 Series

- Varied diode powers
- Binocular sensors
- Available with Red, Blue or IR laser diodes
- Accuracy ± 0.05% working range

OPTIONS

- Protective housing with air and water cooling
- Custom versions with non-standard base, range or housing shape
- Special version for use in high vibration conditions
- Special flexible cable for robotic applications
- Variants with round and elliptical spot







SOFTWARE

- Setting sensor parameters
- Receiving, storage, visualization
- Speed and acceleration calculation



| | RF603- | R-X/4 X/2 X/5 X/10 X/15 X/25 X/30 X/50 X/100 X/250 X/500 X/750 X/1000 X | | | | | | | | X/1250 | | | | | |
|-------------|---|---|--|----------|--------------|--------------|--------------|--------------|---------------|---------------|-----|------|--------|-----------|-----|
| Bas | e distance X, mm | 39 | 15 | 15 | 15, 25 60 | 15, 30 65 | 25, 45 80 | 35, 55 95 | 45, 65 105 | 60, 90 140 | 80 | 125 | 145 | 245 | 260 |
| Mea | surement range, mm | 4 | 4 2 5 10 15 25 30 50 100 250 500 7 | | | | | | | | 750 | 1000 | 1250 | | |
| Line | arity, % | | ±0.05 of the range | | | | | | | ±0.1 | | | | | |
| Res | olution, % | | | | (| 0.01 of the | e range (fe | or the digi | tal output | only) | | | | 0. | 02 |
| Tem | perature drift | | 0.02% of the range/°C | | | | | | | | | | | | |
| Max freq | a measurement uency, Hz | | 9400 | | | | | | | | | | | | |
| Ligł | it source | | red semiconductor laser, 660 nm wavelength or UV semiconductor laser 405/450 nm wavelength (BLUE version) | | | | | | | | | | | | |
| | model | RF603 | | | | | | | | | | | | | |
| | output power | ≤0.2 | ≤0.2 ≤3 mW | | | | | | | | | | | | |
| | laser safety Class | 1 | 1 3R (IEC60825-1) | | | | | | | | | | | | |
| arrce | model | | | | | | R | F603L | | | | | | | |
| it sol | output power | | | | | | ≤0 | .95 mW | | | | | | | |
| Ligh | laser safety Class | | | | | | 2 (IE | C60825-1 |) | | | | | | |
| | model | | | | | | | | | | | | RF | 603P | |
| | output power | | | | | | | | | | | | ≤2 | 0 mW | |
| | laser safety Class | | | | | | | | | | | | 3B (IE | C60825-1) | |
| Wei | ght (without cable) | | | | | | | | 100 | | | | | | |
| Not | e 1: RF603-R-39/4 sensor is designed to use | with mirror s | urfaces an | d alass. | | | | | | | | | | | |



HIGH SPEED SENSORS

RF603HS Series

- Universal high-speed compact laser sensors
- Sampling rate up to 70 kHz
- Available with Red and Blue laser diodes
- Ideal for registration of high speed events and vibration measurement

| RF603HS- | X/2 | X/5 | X/10 | X/15 | X/25 | X/30 | X/50 | X/100 | X/250 | X/500 | X/750 |
|---------------------------------|--|-----|--------------|--------------|--------------|--------------|---------------|---------------|-------|-------|-------|
| Base distance X, mm | 15 | 15 | 15, 25 60 | 15, 30 65 | 25, 45 80 | 35, 55 95 | 45, 65 105 | 60, 90 140 | 80 | 125 | 145 |
| Measurement range, mm | 2 | 5 | 10 | 15 | 25 | 30 | 50 | 100 | 250 | 500 | 750 |
| Max. measurement frequency, kHz | 70 | | | | | | | | | | |
| Linearity, % | ± 0.1 (70 kHz) of the range | | | | | | | | | | |
| Resolution, % | 0.01 (70 kHz) of the range | | | | | | | | | | |
| Temperature drift | 0.02% of the range/°C | | | | | | | | | | |
| Light source | red semiconductor laser (660 nm wavelength) or blue semiconductor laser (405/450 nm wavelength) | | | | | | | | | | |
| Output power | ≤4.8 mW ≤20 mW ≤80 mW | | | ≤80 mW | | | | | | | |
| Laser safety Class | 3R (IEC/EN 60825-1:2014) 3B (IEC/EN 60825-1:2014) | | | -1:2014) | | | | | | | |
| Weight (without cable) | | | | | | 110 |) | | | | |

LARGE-BASE AND LONG RANGE SENSORS

RF600 Series

- High-precision measurement of the position of remote objects
- High-speed (70 kHz) sensors





| RF600- | X/10 | X/30 | X/40 | X/100 | X/250 | X/500 | X/600 | X/1000 | X/1000 | X/1500 | X/2000 | X/2500 | X/20 | X/50 |
|----------------------------|------|--|------|-------|-------|-----------|-------|------------|--------|--------|--------|--------|------|------|
| Base distance X, mm | 230 | 300 | 330 | 500 | 230 | 300, 1000 | 230 | 1300 | 380 | 390 | 410 | 420 | 540 | 535 |
| Measurement range, mm | 10 | 30 | 40 | 100 | 250 | 500 | 600 | 1000 | 1000 | 1500 | 2000 | 2500 | 20 | 50 |
| Max. measurement frequency | | 9.4 kHz, 70 kHz | | | | | | | | | | | | |
| Linearity, % of the range | | ±0.05 ±0.1 ±0.0 | | | | | | | .05 | | | | | |
| Resolution, % of the range | | 0.01 of the range (digital output only) 0.03 0.01 | | | | | | 01 | | | | | | |
| Temperature drift | | 0.02% of the range/°C | | | | | | | | | | | | |
| Light source | | red semiconductor laser, 660 nm wavelength or UV semiconductor laser 405/450 nm wavelength (BLUE version) | | | | | | | | | | | | |
| Output power | | ≤4.8 mW 80 mW | | | | | | | | | | | | |
| Laser safety Class | | 3R (IEC60825-1) 3B | | | | | | 3B (IEC608 | 25-1) | | | | | |
| Weight (without cable) | | 500 | | | | | | 20 | 00 | | | | | |

SUPER COMPACT LASER SENSORS

RF602 Series

Unique combination of dimensions, performance and operating ranges



| | IO | | | | | | | |
|------------------------------|-------|--|-------|--------|--------|---------|--|--|
| | | | | | | | | |
| RF602- | 20/10 | 20/25 | 30/50 | 50/100 | 65/250 | 105/500 | | |
| Base distance X, mm | 20 | 20 | 30 | 50 | 65 | 105 | | |
| Measurement range, mm | 10 | 25 | 50 | 100 | 250 | 500 | | |
| Max. measurement frequency | | 9400 Hz | | | | | | |
| Linearity, % of the range | | ±0.05 | | | | | | |
| Resolution, % of the range | | 0.01 (digital output only) | | | | | | |
| Temperature drift | | 0.02% of the range/°C | | | | | | |
| Light source | UV se | red semiconductor laser, 660 nm wavelength or UV semiconductor laser 405/450 nm wavelength (BLUE version) | | | | | | |
| Output power, mW | | ≤0.95 mW | | | | | | |
| Laser safety Class | | 2 (IEC60825-1) | | | | | | |
| Weight (without cable), gram | | | | 40 | | | | |

3

SPECIALIZED LASER SENSORS FOR PAVEMENT PROFILE AND TEXTURE MEASUREMENT

RF60i Series

- Accuracy ± 0.03% of working range
- Sampling rate up to 70 kHz

| MODEL | SPECIFIC FEATURES | ASSIGNMENT |
|-----------------------------------|--|--|
| RF603P-125/500 RF603P-245/1000 | high resistance to solar radiationstable operation on wet surfaces | Pavement profile |
| RF607-195/500 | 70 kHz operating frequency round laser spot, diameter <1 mm | measurement |
| RF607-210/230 RF607-230/250 | 70 kHz operating frequency round laser spot, diameter <0.8 mm accuracy ±0.03% of the range | |
| RF603Txt-30/30 | reduced triangulation angle round laser spot, diameter <60 μm simultaneously obtaining profile and image of the surface | Pavement roughness (texture) measurement |





LASER TRIANGULATION PROBES, RF60x SERIES

LASER TRIANGULATION PROBES

Smallest triangulation sensor on the market

- Probe diameter from 8.5 mm
- Measured inner diameter from 9 mm
- Accuracy from ±2 μm
- Sampling rate up to 9.4 kHz
- Probes with BLUE laser
- to control reflecting and semitransparent objects
- Probes with built-in slip ring
- Probes with Wi-Fi





RF609, RF609Rt and RF609Wi-Fi Series

Contactless measurement of inner diameter, ovality, coaxiality, cylindricity and shape of holes, tubes, hosepipes, bushes, gun barrels, etc.



The probe is inserted into the hole and probe or sample is driven in rotation. Laser triangulation sensor built in the probe measures the distance to the hole wall synchronously with the rotation angle. The set of the polar surface coordinates allows to calculate the required parameters. Additional linear translation allows to build 3D model of the hole.

| Parameter (Rt version – sensor with built-in sleep ring) | RF609 (609Rt)- 9/19 | RF609 (609Rt)- 16/48 | | | |
|---|-------------------------------------|-------------------------|--|--|--|
| Measured diameters, mm | 919 | 1648 | | | |
| Diameter measurement accuracy, µm | ±2 | ±10 | | | |
| Sensor measurement frequency, Hz | 9400 | | | | |
| Rotational speed for Rt version, no more rps | 4 | | | | |
| Laser safety Class | 2 (IEC60825-1) | | | | |
| Interface | RS232 or RS485 or Ethernet or Wi-Fi | | | | |
| Synchronization input: trigger, A-B encoder, V | 2.4-24 | | | | |
| Minimal distance to the hole bottom, mm | 20 | | | | |
| Hole depth, mm | by request | | | | |
| Power supply, V | 936 | | | | |
| Power consumption, W | 1.5-2 | | | | |
| * for other measured diameters and hele death ranges please consult fastery | | | | | |

* for other measured diameters and hole depth ranges please consult factory



RF609Rt-9/19



ABSOLUTE LINEAR ENCODERS, RF25x SERIES

ABSOLUTE LINEAR POSITION SENSORS (ABSOLUTE LINEAR ENCODERS)

RF25X Series

Absolute linear encoders are designed for measuring and checking displacements, dimensions, run-outs, surface profiles Innovative technology of absolute measurement and deformations of engineered objects. Measuring ranges from 3 to 55 mm 0.1 µm resolution **Emulation of incremental encoder signals** (6 RF251 CMOS sensor reads the signal from the scale Quarz Glass Scale carries special positional pattern 253 124 87 LED RF256 forms parallel beam Processor calculates scale position



| RF | 25X- | RF251-3 | RF251-25 | RF256-15 | RF256-35 | RF256-55 | | | |
|------------------------------|---------|--|---|--|----------|----------|--|--|--|
| Measurement range, mm | | 3 | 25 | 15 | 35 | 55 | | | |
| Accuracy (at T=20 °C), µm | | | ±3 | | | | | | |
| Resolution, µm | | 0.1 or 0.5 or 1 or 5 or 10 | | | | | | | |
| Output interface | digital | RS422 | (EncD5 or En | (RS485 and SSI or RS232) and ncD10 – emulation of quadrature signals of incremental trans-ducers) | | | | | |
| | analog | no | | 020 mA (<500 Om load) or 010 V | | | | | |
| Synchronization input | | n | 10 | opto-isolated | | | | | |
| Logical outputs | | no | 10 two outputs, NPN: 100 mA max; 40 V max | | | | | | |
| Indication | | no two-color LED (red/green) | | | | | | | |
| Power supply, V | | 12 (without analogue output) 15 (with analogue output) | | | | | | | |
| Power consumption, W | | 0.75 | | | | | | | |
| Enclosure rating | | IP57 | | IP | 50 | | | | |
| Operating temperature, °C | | -40+50 | -10+50 | | | | | | |
| Weight (without cable), gran | n | 70 | 110 | 110 | 150 | 180 | | | |

OPTICAL MICROMETERS, RF65x SERIES

OPTICAL MICROMETERS

RF65X Series

PURPOSE

Contactless diameter, gaps and technological object position measurement.

WORKING PRINCIPLE

The micrometer operation is based on the so-called 'shadow' principle. The micrometer consists of two blocks – transmitter and receiver. Radiation of a semiconductor LED is collimated by a lens. With an object placed in the collimated beam region, shadow image formed is scanned with a photo-detector array. A processor calculates the position (size) of the object from the position of shadow border (borders).

MODELS

RF651 — universal micrometers

RF656 — high-precision micrometers with telecentric optics

RF656XY and RF656.3 — two and three axis micrometers

RF656.2D — 2D optical micrometers

RF659 — edge sensors

MAIN FEATURES

- Measurement range from 5 to 100 mm
- Up to ±0.3 μm accuracy
- Up to 10 000 Hz sampling rate
- RS232/RS485/Ethernet +4...20 mA/0...10V
- Micrometers with telecentric lens
- Mutual synchronization of the sensors (master-slave) for multi-axis measurement tasks
- Service Software for micrometers parameterization
- Free SDK and examples for Windows, Linux, .NET, MATLAB, LabVIEW
- Dual, three and multi axis Micrometers
- Air-knife window protection





OPTICAL MICROMETERS, RF65x SERIES



RF656 TWO AND THREE AXIS MICROMETERS. TWIN MICROMETERS

The parameters for each axis of the micrometer match to the parameters of the corresponding single-axis micrometer, see Table above.



RF656XY-25



RF656XY-5



RF656XY-50



OPTICAL MICROMETERS, RF65x SERIES



RF656.3-25





RF656TWIN-75

RF656 TWO AND THREE AXIS MICROMETERS. TWIN MICROMETERS



SOFTWARE



EDGE AND DIAMETER SENSORS

RF659 Series

The sensors are intended for non-contact measuring and monitoring the position of the edge (edges) of various objects, such as tapes, plates, substrates, etc.





| Distance between transmitter and receiver | 30 mm |
|---|----------|
| | 50 11111 |
| Measurement range | 7 mm |
| Accuracy | ±20 μm |

www.riftek.com

2D OPTICAL MICROMETERS, RF656.2D SERIES

PURPOSE

Micrometers are designed for non-contact two-dimensional measurements of linear dimensions, diameters, angles, thread pitch, shape of parts, etc.

WORKING PRINCIPLE

The micrometer operation is based on the so-called shadow principle. The micrometer consists of two parts - an emitter and a receiver. The light from the LED is collimated by the lens. When placing an object in the area of the collimated beam, the resulting shadow image of the object is scanned by a 2D CMOS sensor. Based on the location of the shadow border, the computer calculates the dimensions of the object.

MAIN FEATURES

- Speed: up to 50 images per second
- Measurements and tolerance control are performed accorfing to an algorithm created by the user from a library of ready-made blocks
- Various combinations of blocks and connections between them make it possible to create an almost unlimited number of measurement functions and measure products of varying complexity
- Support for Ethernet/IP, Modbus TCP, UDP protocols
- Logical outputs for controlling actuators and signaling the validity of the product



| RF656.2D | -8x10 | -25x30 | -30x40 | -40x50 |
|---------------------------------|-------|--------------|---------------|--------|
| Measurement range, mm | 8x10 | 25x30 | 30x40 | 40x50 |
| Measurement accuracy, um | ±1,5 | ±2,5 | ±3 | ±4,5 |
| Smallest detectable object, mm | 0,07 | 0,2 | 0,25 | 0,35 |
| Measurement frequency, Hz | | 130 (50 with | n triggering) | |
| Dimension B, see drawings below | 20100 | 20259 | 20250 | 20500 |
| Controller | | Smart | Unit-M | |
| Weight, not less, kg | 1,1 | 2,3 | 2,8 | 5,6 |





RF656.2D-8x10



RF656.2D-40x50



PURPOSE

Non-conact measuring and checking of surface profile, dimensions, deformations, flatness, gaps, volume, 3D models construction.

WORKING PRINCIPLE

Profiler operation is based on the principle of optical triangulation.

Radiation of a semiconductor laser is formed by a lens in a line and projected to an object. Radiation scattered from the object is collected by the lens and directed to a two-dimensional CMOS image sensor. The image of object outline thus formed is analyzed by a signal processor, which calculates the distance to the object (Z-coordinate) for each point of the set along the laser line on the object (X-coordinate). Profilers are characterized by base distance (beginning of the range), SMR, for Z-coordinate, measuring range (MR) for Z-coordinate, measuring range for X-coordinate at the beginning of Z (Xsmr) and measuring range for X-coordinate at the end of Z (Xemr).

MODELS

RF627Smart — profilers with in-built measurement functions and industry protocols

RF627BiSmart — dual-camera profilers with in-built measurement functions and industry protocols

RF628 — high speed profilers

RF629 — high speed profilers with increased resolution

RF6292 — high speed profilers with increased resolution and increased "laser line length/range" ratio

RF627Smart-Weld — profilers for welding robots with in-built functions of weld seam tracking and measurement

RF627AVIKScan — hand-held profilers for weld seam geometry control

MAIN FEATURES

- Measuring ranges from 10 to 1010 mm
- 0.01% linearity
- Sampling rate up to 16000 profiles/s
- Profilers with RED, BLUE and IR lasers
- Laser Safety Class 2M
- Dual camera profilers
- Trigger and encoder synchronization, mutual synchronization
- WEB-interface
- Free SDK and examples for Windows, Linux, .NET, MATLAB, LabVIEW
- Specialized profilers for hole control
- Profilers with air and water cooling
- Profilers with powerful lasers (1.2W red, 1.5W blue, 10W IR)
- Built-in standard industrial protocols and interfaces for robots



Focusing lens



www.riftek.com

SOFTWARE

INTEGRATED WEB-INTERFACE for profilers parameterization, image and profile visualization



Data receiving, storage, visualization





SMART-PROFILERS



RF627Smart profilers makes it possible to measure geometric parameters of the object profile in real time directly in the profiler without connecting to a computer. Analysis, calculations, measurements, tolerance control are carried out according to the algorithm created by the user. To build the algorithm, a simple and intuitive tool is provided - a computation graph. The graph is formed from a library of ready-made blocks. Various combinations of blocks and connections between them allow the user to create an almost unlimited number of measuring functions, as well as to process profiles of any complexity. Measurement results can be transmitted via various protocols (Ethernet/IP, Modbus TCP, UDP), as well as to the logic outputs of the profiler in order to control the actuators and notify about product suitability.

RF62x Basic technical data

| Laser | 660 nm or 405 nm or 450 nm 808 nm Class 2M no IEC/EN 60825-1:2014 or Class 3B on request | | | | |
|-----------------------------------|---|--|--|--|--|
| Interface | Ethernet / 1000 Mbps | | | | |
| Synchronization inputs | RS422, 3 channels | | | | |
| Laser on/off hardware input | 1 | | | | |
| Outputs | RS422, 1 channel | | | | |
| Power supply | 930 V or 1236 V for profilers with Blue laser | | | | |
| Power consumption, not more | RF627Smart - 6 W (without a built-in heater) RF627BiSmart - 11 W, RF628 - 17 W RF629 и RF6292 - 17 W | | | | |
| Environment resistance | | | | | |
| Enclosure rating | IP67 | | | | |
| Vibration | 20 g / 101000 Hz, 6 hours for each of XYZ axes | | | | |
| Shock | 30 g/6 ms | | | | |
| Operating ambient temperature, °C | -20+40, or -40+40 for profilers with built-in heater, or -40+120 for profilers with built-in heater and cooling system | | | | |
| Relative humidity | 5-95% (no condensation) | | | | |
| Storage temperature, °C | -20+70 | | | | |
| Housing/windows material | aluminum/glass | | | | |



SMART PROFILERS

RF627Smart Series

| | | | | | Overall specifi | ications | | | |
|--------------------|---|---------|---------|----------|-----------------|--------------|------------|-----------|------|
| Sampling rate, Hz | Full range: 485 or 921 (DS mode), ROI: 4884 or 6379 (DS mode) | | | | | | | | |
| Linearity Z, %FS | | | | | 0.0 | 1 or 0.02 fe | or DS mode | | |
| Resolution, X axis | | | | | 648 or 129 | 6 points (pi | ogrammable | value) | |
| Range | MR, mm | SMR, mm | EMR, mm | Xsmr, mm | Xemr, mm | Size | e, mm | Weight, g | |
| 25/10-8/11 | 10 | 25 | 35 | 8 | 11 | Fig. 1 | | 0.37 | |
| 65/25-20/22 | 25 | 65 | 90 | 20 | 22 | | | | |
| 75/50-30/41 | 50 | 75 | 125 | 30 | 41 |] | | | |
| 70/100-48/82 | 100 | 70 | 170 | 48 | 82 | | | 0.6 | L |
| 70/150-58/122 | 150 | 70 | 220 | 58 | 122 | Fig. 2 | | | SMR |
| 95/150-53/106 | 150 | 95 | 245 | 53 | 106 | | | | Xsmr |
| 82/200-60/150 | 200 | 82 | 282 | 60 | 150 |] | | | |
| 90/250-65/180 | 250 | 90 | 340 | 65 | 180 | | | | |
| 180/250-170/278 | 250 | 180 | 430 | 170 | 278 | | L=326 | 2 | |
| 190/300-160/300 | 300 | 190 | 490 | 160 | 300 | | L=283 | 1.9 | |
| 220/300-203/330 | 300 | 220 | 520 | 203 | 330 | | L=374 | 2.1 | MR |
| 260/400-210/400 | 400 | 260 | 660 | 210 | 400 | | L=350 | 2.2 | |
| 325/500-268/500 | 500 | 325 | 825 | 268 | 500 |] | L=415 | 2.3 | |
| 400/600-320/600 | 600 | 400 | 1000 | 320 | 600 | Fig. 3 | L=490 | 2.4 | |
| 475/700-374/700 | 700 | 475 | 1175 | 374 | 700 |] | L=558 | 2.5 | |
| 545/800-425/800 | 800 | 545 | 1345 | 425 | 800 |] | L=627 | 2.6 | Xemr |
| 615/900-480/900 | 900 | 615 | 1515 | 480 | 900 |] | L=696 | 2.7 | Xem |
| 690/1000-535/1000 | 1000 | 690 | 1690 | 535 | 1000 | | L=765 | 2.8 | |
| 620/1165-430/1010 | 1165 | 620 | 1785 | 430 | 1010 | | L=554 | 2.5 | |









Figure 1

DUAL CAMERA PROFILERS

RF627BiSmart Series

Figure 3

- Profilers with a single laser and two receiving cameras for high-quality 3D model generation
- Sampling rate (full working range) 520 profiles/s
- Resolution, X axis (combined profile) 1456 or 2912 points
- **Full support for Smart functions**

| Range | MR, mm | SMR, mm | EMR, mm | Xsmr, mm | Xemr, mm |
|---------------|--------|---------|---------|----------|----------|
| 65/25-20/22 | 25 | 65 | 90 | 20 | 22 |
| 75/50-30/41 | 50 | 75 | 125 | 30 | 41 |
| 70/100-48/82 | 100 | 70 | 170 | 48 | 82 |
| 70/150-58/122 | 150 | 70 | 220 | 58 | 122 |
| 95/150-53/106 | 150 | 95 | 245 | 53 | 106 |
| 82/200-60/150 | 200 | 82 | 282 | 60 | 150 |
| 90/250-65/180 | 250 | 90 | 340 | 65 | 180 |



3D model of a conical hole, monocular profiler





3D model of a conical hole, binocular profiler

HIGH SPEED PROFILERS

RF628 Series

- Sampling rate (full working range) > 4000 profiles/sec
- Sampling rate (ROI mode) – up to 16000 profiles/sec
- Linearity, Z axis 0.01% of the range
- Resolution, X axis 640 or 1280 points

| Range | MR, mm | SMR, mm | EMR, mm | Xsmr, mm | Xemr, mm |
|------------------|--------|---------|---------|----------|----------|
| 65/10-11/12 | 10 | 65 | 75 | 11 | 12 |
| 75/25-20/22 | 25 | 75 | 100 | 20 | 22 |
| 90/50-32/44 | 50 | 90 | 140 | 32 | 44 |
| 125/75-42/58 | 75 | 125 | 200 | 42 | 58 |
| 150/100-50/74 | 100 | 150 | 250 | 50 | 74 |
| 150/150-64/112 | 150 | 150 | 300 | 64 | 112 |
| 210/300-148/276 | 300 | 210 | 510 | 148 | 276 |
| 285/400-198/376 | 400 | 285 | 685 | 198 | 376 |
| 370/500-250/466 | 500 | 370 | 870 | 250 | 466 |
| 450/600-300/556 | 600 | 450 | 1000 | 300 | 556 |
| 530/700-350/650 | 700 | 530 | 1230 | 350 | 650 |
| 610/800-400/744 | 800 | 610 | 1410 | 400 | 744 |
| 685/900-450/836 | 900 | 685 | 1585 | 450 | 836 |
| 765/1000-500/930 | 1000 | 765 | 1765 | 500 | 930 |



HIGH SPEED PROFILERS WITH INCREASED RESOLUTION

RF629, RF6292 Series



RF629

- Sampling rate (full working range) 1000 Hz
- Sampling rate (ROI mode) 16000 Hz
- Resolution, X axis 1280 or 2560 points Linearity, Z axis 0.01%

| Range | MR, mm | SMR, mm | EMR, mm | Xsmr, mm | Xemr, mm |
|-------------------|--------|---------|---------|----------|----------|
| 60/25-22/26 | 25 | 60 | 85 | 22 | 26 |
| 60/50-36/50 | 50 | 60 | 110 | 36 | 50 |
| 65/100-56/100 | 100 | 65 | 165 | 56 | 100 |
| 90/150-70/140 | 150 | 90 | 240 | 70 | 140 |
| 110/200-84/178 | 200 | 110 | 310 | 84 | 178 |
| 95/250-100/250 | 250 | 95 | 345 | 100 | 250 |
| 190/300-120/300 | 300 | 190 | 490 | 120 | 300 |
| 145/400-158/400 | 400 | 145 | 545 | 158 | 400 |
| 180/500-198/500 | 500 | 180 | 680 | 198 | 500 |
| 230/600-236/600 | 600 | 230 | 830 | 236 | 600 |
| 265/700-274/700 | 700 | 265 | 965 | 274 | 700 |
| 310/800-314/800 | 800 | 310 | 1110 | 314 | 800 |
| 345/900-352/900 | 900 | 345 | 1245 | 352 | 900 |
| 375/1000-392/1000 | 1000 | 375 | 1375 | 392 | 1000 |



RF6292

- Specialized profilers with Xend/Z ratio >2/5
- Sampling rate (full working range) > 4000 Hz
- Resolution, X axis 1280 or 2560 points
- Linearity, Z axis 0.01%

| Range | MR, mm | SMR, mm | EMR, mm | Xsmr, mm | Xemr, mm |
|-----------------|--------|---------|---------|----------|----------|
| 70/5-24/24 | 5 | 70 | 80 | 24 | 24 |
| 80/15-40/44 | 15 | 80 | 95 | 40 | 44 |
| 95/25-70/81 | 25 | 95 | 120 | 70 | 81 |
| 135/35-90/105 | 35 | 135 | 170 | 90 | 105 |
| 170/45-110/130 | 45 | 170 | 215 | 110 | 130 |
| 170/75-146/194 | 75 | 170 | 245 | 146 | 194 |
| 220/90-200/256 | 90 | 220 | 310 | 200 | 256 |
| 355/120-302/376 | 120 | 355 | 575 | 302 | 376 |
| 455/170-400/500 | 170 | 455 | 625 | 400 | 500 |
| 550/225-500/624 | 225 | 550 | 775 | 500 | 634 |

LASER SEAM TRACKING SYSTEM FOR WELDING AUTOMATION

LASER PROFILERS FOR WELDING ROBOTS

RF627SMART-WELD SERIES



MAIN FEATURES

- RF627Smart-Weld laser profilers with direct connection to the robot controller
- Real-time recognition, tracking, and measurement
- Works with all surfaces, including shiny ones
- Connection to all common robot controllers

| Laser | Profilers | RF627S | mart-W | eld Serie | es. Working ranges |
|---|------------|-----------|-------------|-------------|--------------------|
| Range | SMR, mm | MR, mm | Xsmr, mm | Xemr, mm | Laser |
| 65/25-20/22 | 25 | 65 | 20 | 22 | |
| 70/50-30/41 | 50 | 70 | 30 | 41 | |
| 76/100-48/82 | 100 | 76 | 48 | 82 | |
| 70/130-40/86 | 130 | 70 | 40 | 86 | Class 2M |
| 250/130-52/76 | 130 | 250 | 52 | 76 | |
| 82/200-60/150 | 200 | 82 | 60 | 150 | |
| 90/250-65/180 | 250 | 90 | 65 | 180 | |
| For the rest parameters — see RF627Smart Series | | | | | |

RF627SMART-WELD







RF627Smart-Weld-70/130-40/86



RF627SMART-WELD CONFIGURATIONS



Profiler for welding robot



Profiler for welding robot with cooling



Profiler for welding robot with protective shutter

www.riftek.com

LASER SEAM TRACKING SYSTEM FOR WELDING AUTOMATION

STEP 1

Connect the equipment according to the functional diagram:

STEP 2

Calibrate the profiler relative to the robot.



STEP 3.2

Using the profiler web interface, create a computation graph from the library of ready-made blocks, taking into account the features of the equipment, namely:



Select a tracking template or create your own using the template editor.



Select a Smart-block of the robot communication protocol.

STEP 4



Clear

Select a Smart-block for the type of tracking:

1. Output values of the smart block

- points and angles to which the actuator should move.

2. Output values of the smart-block linear and angular velocities with _ which the actuator should move.



Add and configure the Smart block for script execution. Complete the construction of the tracking graph.



Observe the process on the computer screen.

HOW IT WORKS

START WORKING

SPECIALIZED SCANNING SYSTEMS FOR WELDS, WELDED JOINTS AND EDGE PREPARATION

RF627AVIKScan



EDGE PREPARATION CONTROL



154

110



DESIGN

MEASUREMENT OF OFFSET, JOINT ANGLE, GAP WIDTH AND ETC.





Measured parameters



width, height, angles, mismatch, undercut and so on

MEASUREMENT OF WELD HEIGHT AND WIDTH, CUTTING DEPTH, CAMBER AND ETC.

3D VISUALIZATION SOFTWARE





www.riftek.com

h

3D LASER MEASUREMENTS

3D LASER SCANNING KIT

SHTRIKH-2 SERIES

3D Laser Scanning Kit is designed for mounting on any type of CNC machine and intended for non-contact scanning of products and obtaining 3D computer-simulated models.

In the scanning mode, the machine CNC system moves the sensor line-by-line over the item prototype. Thus, XYZ coordinate array for the surface is formed, i.e. a digital prototype model is created which is saved as a point cloud file as well as in a common STL format suitable for subsequent use in CNC.

| Parameter | Value |
|----------------------------------|---------------|
| Materials to be scanned | any material |
| Size of scanning area | arbitrary |
| Average scanning speed, points/s | up to 100 000 |

3D LASER MEASUREMENT MACHINE

RF1010SS

3D measuring machine is designed for non-contact measurement of geometrical parameters of objects, specifically sunflower seeds. Laser scanner RF625 Series, that is installed in the machine, scans the objects and identifies it's geometry. As result of scanning we get the parameters of every sunflower seed and their total quantity.



| Parameter | Value |
|-------------------------------------|-------|
| Nominal sampling rate, profiles/sec | 250 |
| Scanning speed, mm/s | 100 |
| Accuracy, µm | ±150 |



3D LASER MEASUREMENT MACHINE

RF1010SL

3D Measurement Machine was specially developed to measure suspension arm's parameters for automotive industry. Laser scanner RF625 Series, which is installed in the machine, scans the suspension arm, measures and controls its geometrical parameters.



| Parameter | Value |
|-------------------------------------|-------|
| Nominal sampling rate, profiles/sec | 250 |
| Scanning speed, mm/s | 50 |
| Accuracy, % of the range | ±0.1 |

3D LASER MEASUREMENT MACHINE

RF1240TB Series

Developed together with MARVIE LLC



3D Measurement Machine is specially designed for control of geometric parameters of large diameter pipes. The machine consists of 24 wide-range high speed synchronized laser scanners type RF625-650 located on the outer circumference of the pipe, which makes it possible to inspect full profile of the pipe in the course of manufacture.



www.riftek.com

3D LASER MEASUREMENTS



3D INSPECTION OF STEEL BAND RIMS



THE SYSTEM ON THE BASE OF ROTATING 2D PROFILER FOR CONTROL OF:

- Inner diameter
- Roundness
- Cylindricity
- Chamfer geometry

| Parameter | Value |
|-----------------|--------|
| ID range, mm | 100400 |
| Heigh range, mm | 70305 |
| Accuracy, mm | ±0,05 |

3D CONTROL OF HAMMERED AXLES SHAPE





Synchronous circular scanning with point laser sensors of the external and internal surfaces of a product, calculation of geometric parameters and comparison with an ideal model.

| Parameter | Value |
|--------------------------|-------|
| ID range, mm | 30143 |
| Accuracy, mm | ±0,05 |
| OD range, mm | 62180 |
| Accuracy, mm | ±0,1 |
| Heigh range, mm | 70305 |
| Depth of measurement, mm | 500 |

3D MEASUREMENT AND CUTTING OF BIOLOGICAL TISSUE



TURNKEY SOLUTION BASED ON A CNC MACHINE EQUIPPED WITH A 2D LASER SCANNER

Non-contact measurement of the thickness distribution of biomaterials intended for the production of blood vessels and heart valves, as well as optimal automated laser cutting.

| Parameter | Value |
|-----------------------------------|-----------------------|
| hickness measurement accuracy, mm | ±0,03 |
| Scanning speed, mm/s | 100 |
| D laser profiler | RF627.Blue-25/10-8/11 |

3D CONTROL OF CHARCOAL BURNERS



The automated laser system is designed to create a complete 3D computer model of the internal surface of the burner and calculate the degree of wear with high accuracy and resolution.

| Parameter | Value |
|-----------------|---------|
| ID range, mm | 4401440 |
| Accuracy, mm | ±0,5 |
| Depth range, mm | 02000 |

Systems are intended for contactless measuring of inner diameter and profiles of gun barrels, cylindrical and taper pipes, progressive cavity stators, turbodrills and so on.

TWO WORKING PRINCIPLES

- Multisensor measurement by stationary laser sensors -RF040 Series
- Inner surface laser scanning by rotating sensors -RF096 Series

SYSTEMS PARAMETERS

- Measured ID from 6 mm
- Up to several µm accuracy
- Up to 32000 measured points on the surface in 2 seconds
- Calculation of ovality and roundness
- Surface defects detection and measurement
- 3D model of inner surface design

SYSTEM STRUCTURE

- Laser measurement module with
 - stationary sensors
 - rotating sensors
- Translation module intended for transportation of measurement module inside the pipe:
 - self propelled
 - any kind of pulling machine
- Software for PC
- Calibration rings

SYSTEM CAN CONTAIN

Centering frame to hold measurement module near pipe axis

OPTIONS

- Pipe straightness measurement module
- Video inspection module
- Wireless connection (Wi-Fi) module



MULTISENSOR MEASUREMENT HEAD

RF040 Series

The Multisensor Measurement Module contains up to 6 laser triangulation sensors located circumferentially in one housing at known fixed angles.

The measurement module is inserted into the pipe and moved by translation module to the definite position.

Calibrated laser sensors measure distances to the inner surface .

Software calculates diameter of the pipe.





LASER MEASUREMENT MODULE FOR CONTROL OF LARGE DIAMETER FIBERGLASS PIPES



| neter | Value |
|-----------------------|-------|
| ter of the module, mm | 70 |
| | |



| Parameter | Value |
|-------------------------------|-------------------------|
| 6 laser triangulation sensors | |
| Diameter range, mm | 65…115 or by request |
| Accuracy, % of range | ±0.1 |
| | |

| Parameter | Value |
|----------------------------|--|
| Diameter of the module, mm | 70 |
| Diameter range, mm | 95195 mm (main range) 160300 mm (extended range) |
| Accuracy, mm | 0.05 mm (main range) 0.2 mm (extended range) |

| Parameter | Value |
|-------------------------------|----------|
| 6 laser triangulation sensors | |
| Diameter range, mm | 500-1250 |
| Accuracy, mm | ±0.2 |
| | |

MULTISENSOR INNER DIAMETER MEASUREMENT SYSTEMS WITH WI-FI MODULE



| Parameter | Value |
|-------------------------------|-------------------|
| ID measurement range, mm | 100150 |
| Accuracy, mm | ±0.05 |
| Measurement speed, ID /s | 500 |
| Light source | Red laser, 660 nm |
| Laser output power, mW | <1 |
| Laser safety Class | 2 (IEC60825-1) |
| Interface | Wi-Fi, USB |
| Time of continuous work, hour | 4 |

ROTATING MEASUREMENT HEAD

RF096 Series



MULTISENSOR MEASUREMENT MODULE CONTAINS

laser triangulation sensor 1 (one or several with different measurement range and stand-off distance), mounted on rotating platform 2, which contains motor 3 with electronic driver 4, and rotary encoder 5 coupled to the motor 3. The system also includes a tilt sensor 6, intended for control of inclination of rotating platform during measurement.

OPTIONS

built-in Wi-Fi module 7 is used for communication between the system and PC; the system can be powered from internal batteries 8.

2D laser scanner can be installed instead of points sensor.

The measurement module is inserted into the pipe and moved by pulling machine to the definite position.

Rotating laser sensor scans inner surface of the pipe and the module transmits polar coordinates of the surface (distance from rotation axis, measured by triangulation sensor and a corresponding angle, measured by encoder).



Software uses the set of transmitted coordinates

- to calculate:
 - ID of measured pipe
 - ovality and roundness
 - to find:

- surface defects
- to design

MOBILE LASER SCANNING SYSTEM FOR

PIPE DIAMETER CONTROL

- Full profile in definite section
- 3D model of the pipe inner surface

WHEEL CENTER BORE INNER DIAMETER MEASURING GAUGE



MODEL RF096-50/70-200-Clb

Non-contact scanning and inner surface geometry measurement of wheel center bore.

| Parameter | Value | |
|--|-------|--|
| Rotating measurement head with 2 sensors | | |
| ID range, mm | 5070 | |
| ID measurement accuracy, μm | ±5 | |
| Depth of measurement, mm | 200 | |
| Autocalibration | | |



- Rotating measurement head with 2 sensors
- Linear scanning along the tube

| Parameter | Value |
|-----------------------------|---------------------------|
| ID range, mm | 146176 |
| ID measurement accuracy, μm | ±10 |
| Depth of measurement, mm | programmable, up to 70 |
| Battery power supply | |
| Built-in Wi-Fi module | |

LASER SCANNING SYSTEMS FOR PIPE DIAMETER CONTROL



| Parameter | Value |
|-----------------------------|-----------------------|
| ID range, mm | 4555 or by request |
| ID measurement accuracy, μm | ±2 |

LEAF SPRING HOLE INNER DIAMETER MEASUREMENT MACHINE

RF096-30/75-120

The machine is designed for contactless scanning and geometrical parameters measurement of the leaf springs holes.



| Parameter | Value |
|-----------------------------|--|
| Measured diameters, mm | 30-75 |
| ID measurement accuracy, mm | ±0.04 |
| Depth of measured hole, mm | 120 |
| Measured parameters | diameter, roundness, conicity, cylindricity |

RF096-Insp

The system is intended for non-contact detection of the debris inside the circular grooves of different technological items, for example brake calipers and so on.

LASER DEBRIS INSPECTION SYSTEM

The system can be used also for groove seal profiling (seal deformation inspection).



| Parameter | Value |
|--------------------------------------|-------------|
| Inspected grooves diameter range, mm | 35-53 |
| Minimal size of detected debris, mm | 0.1x0.1x0.1 |
| Laser sensor linearity, µm | ±10 |
| Depth of measured hole, mm | 120 |
| Inspection time, s | 1.2 |

PIPES ID MEASUREMENT MACHINE

RF096-9/16-800

The machine is designed for contactless scanning and geometrical parameters measurement of small diameter pipes.



| Parameter | Value |
|--------------------------|-----------|
| ID measurement range, mm | 919 |
| Accuracy, mm | ±5 |
| Pipe length, mm | Up to 800 |

PIPES ID MEASUREMENT MACHINE

RF096-35/50-100

The machine is designed for in-line contactless scanning and geometrical parameters measurement of small diameter pipes.



| Parameter | Value |
|--------------------------|-----------|
| ID measurement range, mm | 3550 |
| Accuracy, mm | ±5 |
| Pipe length, mm | Up to 100 |



The system is designed for well inspections

IP67 Enclosure rating

| Parameter | Value |
|--------------------------------------|--------|
| ID range, mm | 105130 |
| Accuracy, um | ±10 |
| Resolution for cross-section, points | 2048 |
| Speed, cross-sections/s | 4 |



PIPE INNER DIAMETER MEASUREMENT MACHINE

MODEL RF096-32/42-100

The machine is designed for contactless scanning and geometrical parameters measurement of inner diameter of pipes, bushes, holes, tubes, and so on.

Application of the machine - large-scale production.

| Parameter | Value |
|-----------------------------------|-------|
| Measured diameters, mm | 3242 |
| ID measurement accuracy, µm | ±5 |
| Depth of measured hole, mm | ≤80 |
| Measurement cycle (5 sections), s | 13 |



HEAT EXCHANGER TUBE SHEETS MEASUREMENT





HANDHELD ID MEASUREMENT GAUGES

Measurement cycle, s

Series RF096-Dmin/Dmax-Lmin/Lmax-HH



| Parameter | Value |
|--------------|--------------|
| ID range, mm | upon request |
| Accuracy, um | ±1020 |

www.riftek.com

3

SPECIAL MEASUREMENT SYSTEMS

THICKNESS MEASUREMENT SYSTEMS

The systems are designed for non-contact control of the thickness of various sheet materials (plastic, metal, rubber).

RF580 - multipoint systems







| Parameter | Value | | |
|---------------------|------------------------|--|--|
| Thickness range, mm | 10 or 25 or customized | | |
| Accuracy, um | ±3 or ±7 or customized | | |
| Scanning range, mm | by request | | |
| Laser sensors | RF603 or RF603HS | | |

THE SYSTEM FOR GYPSUM BOARDS DIMENSIONAL MEASUREMENT

3DGipsumB





Three measuring stations installed along the conveyor are designed to measure:

- Edge angle
- Shoulder
- Taper length and depth
- Board width and thickness
- Groove and Rim dimensions

| Parameter | Value |
|------------------------------------|--------------|
| Width range, mm | 4001400 |
| Thickness range, mm | 245 |
| Width measurement accuracy, mm | ±0.1 |
| Thickness measurement accuracy, mm | ±1 |
| Profile measurement accuracy, mm | ±0.1 |
| Laser sensors | RF627, RF603 |

www.riftek.com

SPECIAL MEASUREMENT SYSTEMS

LAMINATED TUBES GEOMETRY MEASUREMENT SYSTEM

The system is designed for contactless scanning and geometrical parameters (outer and inner diameter, foil thickness, weld width, tube length) measurement of laminated tubes, made of PBL and ABL foil.



| Parameter | Value |
|---|----------|
| Measured diameters, mm | 1350 |
| Diameter measurement accuracy, µm | ±10 |
| Foil thickness range, mm | 0.050.5 |
| Foil and weld thickness measurement accuracy, μm | ±5 |
| Tube length measurement accuracy, mm | ±0.1 |
| Interface to PC | Ethernet |
| Power supply | 220 |

ONLINE SYSTEMS FOR CONTROL AND REGULATION OF DIAMETER

The systems are designed for non-contact measurement, control and regulation of diameter of technological objects (wire, fiber, hoses, tubes, rods, sausage casings) during their production.



| Parameter | Value |
|-------------------------------|---------|
| Measured diameters, mm | 0.3100 |
| Accuracy, μm | from ±1 |
| Number of controlled sections | up to 6 |

- LASER SYSTEMS FOR SHEET MATERIALS THICKNESS CONTROL
- RF590 Width Measurement System



ADVANTAGES

- Manufacturing process optimization
- Continuous quality monitoring

AUTOMATED SYSTEMS FOR MOTOR SHAFTS MEASUREMENT

The systems are designed for the measurement and control of motor shafts.



| Parameter | Value |
|------------------------|------------------------|
| Measured diameters, mm | 0.1100 (or on request) |
| Measurement error, µm | ±2 |
| Length | on request |

JOHNSON FILTERS INSPECTION MACHINE

The inspection machine is designed to control the inter-wire gap along the length of the well filter.



| Parameter | Value |
|---------------------|-------|
| Filter length, mm | 1000 |
| Gaps range, mm | 0.052 |
| Accuracy, mm | ±0.01 |
| Scanning speed mm/s | 100 |

www.riftek.com

SPEED AND DISTANCE SENSORS

SPEED AND DISTANCE SENSORS

ISD-3 & ISD-5 Series

The sensors are intended for automotive and industrial application for precise contactless measurement of speed and length of nearly any moving object.

Designed for use in automobile and railway transport, metallurgy, cable, chemical, pulp and paper, textile and wood industries, in automated control systems, cutting and accounting systems.







| ISD-3 Parameter | Value | Comments | |
|---|---|---|--|
| Speed range, Km/h | 0.4 – 200 | At TTLout 400 Hz per m/s. Others on request | |
| Speed accuracy | ±0.2 % RMS | Determined on test bench (treadmill) at 18.38 km/h | |
| Absolute distance accuracy* | ±0.2 % RMS | After calibration at S >100 m | |
| Measuring frequency, Hz | 22 | | |
| Nominal distance to the road and tolerance (range of working dis- tance), mm | 280 ± 140 (140 - 420) | Up to 800 mm on request | |
| System power supply (tolerance) | 12 V nominal (11 – 14.5V) | | |
| System power consump- tion, Wt | Sensor head: 10 Wt Processor unit: 5 Wt | | |
| Sensor head operation temperature range, °C | -20+50 | | |
| Weight of the sensor + mounting bracket, g | 280 + 120 | Without cable | |
| Weight of the processor unit, g | 400 | | |
| Sensor dimensions, mm | Ø55 x 205 + illuminator | | |
| Processor unit dimensions, mm | 120x100x35 | | |
| Sensor cable length, m | 2.5 | Up to 10 m on request | |
| System power cable length, m | 2 | Up to 10 m on request | |
| Environmental sensor head protection | IP67 | | |
| Magnetic fixing tool | 4 magnets x 16 Kg strength | | |
| Output signal | TTL (SMOS) 0 – 5 V mean- der type, 400 Hz per m/s (=400 pulses/m) | Others on request | |





| ISD-5 Parameter | ISD-5 Standard | ISD-5 Mini | Comments |
|--|---|---------------------------|---|
| | | | Typical values The loss nemi |
| Speed range, m/s | 0.02 - 20 | 0.005 - 5 | nal working distance the less min and max speed range |
| Speed accuracy*, % RMS | ±0.07 ±0.02 | ±0.15 ±0.05 | No signal averaging With averaging 0.2 - 0.3 s, at V > 1 m/s |
| Length accuracy*, % RMS | <±0.05 | <±0.1 | While pre-calibration for path lengths > 2 m |
| Measuring frequency, Hz | 16 - 5 | 4 | |
| Nominal distance to the object (tolerance), cm | 10, 20, 30, 50, 75, 100 | 10, 15, 20 | Could be noted at ordering |
| Distance tolerance | ±20-25% of | nominal | Depends on the surface (on the edge of the range signal decreased) |
| Emitter type, mW | Visible or IR c.v. laser, 5 – 120 | Visible c.v. laser, <5 | class 3B – 3R |
| Power supply, V | 12 (8 - 14) | | Internal linear voltage regulators +5V in sensor and controller unit |
| Power consumption, Wt: | | | |
| Sensor | 0.5 - 2 | 0.5 | |
| Controller unit | 1 | | |
| Temperature working range, °C | +15+50 | | -10+50 – with active ther- mostabilization option): -50+80°C with protect air cooling housing (option) |
| Sensor weight, g | 320 | 70 | |
| Sensor size, mm | 85x79x46 | 58x43x30 | Without connector, blend and fixing holes |
| Cable length from sensor to controller unit, V | 1.8 or 3 | | Standard cable RS-232 or VGA with DB9 connectors are used. To extend a length it is possible to connect cables sequential |
| Sensor environmental protection | IP67 | | |
| Controller unit: | | | |
| Dimensions, mm | 120x100 |)x35 | |
| Weight, g | 350 | | |
| Analog out: | Length, 2000 pulces/m (=speed 2000 Hz/(m/s), meander 0 – 3 V, TTL compatible, up to 200 KHz | | Typical values, user adjusta- ble (see software description below) |
| Frequency out: | Ethernet (UDP | protocol) | Others on request |
| Digital out: | | | |
| Physical data latency at measurement freq, ms 54 Hz 16 Hz | 9 31 | | Stable, $=\frac{1}{2}$ of measuring time, without averaging |
| Base Software | Program to read data via Ethernet, visualization and saving data, Program for sensor diagnostics, Read data example (LabView 8.2.1 and higher), Dynamic library (DLL) to read data via Ethernet, Sensor parameters configuranion via any libraret browser | | Custom software by request are possible |



RAILWAY WHEEL PROFILE GAUGE

The laser profilometer is designed for measuring

- flange thickness, slope and height, rim/tire thickness,
 - full profile scanning and analyze of wheel rolling surface,
- maintaining of electronic wear data base,
- control of tolerances and sorting in the course of checkup, examination, repair and formation of railway wheel sets.

The device is supplied with database and software package for wheel sets wear data storage and processing.

Measurements are made directly on rolling stock without wheel set roll-out.

| Parameter | Value | |
|--|---|--|
| Measurement range flange heigh, mm | 2045 | |
| -"- flange thickness, mm | 2050 | |
| -"- flange slope, mm | 115 | |
| -"- rim thickness, mm | 36100 (3090) | |
| -"- diameter (calculation method), mm | 4001400 | |
| Measurement error flange height, mm | ± 0.03 | |
| -"- flange thickness, mm | ± 0.03 | |
| -"- flange slope, mm | ± 0.1 | |
| -"- rim thickness, mm | ± 0.1 | |
| -"- diameter, mm | ± 0.1 | |
| Discreteness of indication all parameters, mm | 0.01 | |
| Profile measurement range, mm | 145 | |
| Discreteness of the profile formation, not worse than, mm | 0.025 (5800 points for profile) | |
| Measurement time, s | adaptive, depending on surface quality, 4 average | |
| Power supply (laser scanning module) | 3,7V, Li-ion rechargeable battery 5400mAh for standard IKP and 2400mAh for Short and SShort | |
| The number of measurements that can be taken before battery recharge is not less than | 5000 for standard IKP and 2200 for Short and Super-short | |
| Laser module battery life time | 5 million measurement cycles | |
| Power supply (PDA) | 3,7V Li-polymer battery 3300mAh | |
| PDA memory capacity | 100 000 measurements | |
| Interface between laser scanning module and PDA | Bluetooth | |
| Working temperature range, °C | -20+50 | |
| Enclosure rating | IP42 or IP64 | |

PDA is intended for control of the laser scanning module, data reception from the scanning module, indication of measurement result, parameter input and data storage.



Operator mounts the laser scanning module onto the wheel to be measured. Having received a command from PDA or PC, the laser module performs noncontact scanning of the wheel surface.

MAIN FEATURES

- User-Friendly Interface;
- Flexible setting of measured Parameters of the Wheel Flange;
- The list of Calculated Parameters:
 - Flange Height, Thickness and Slope,
 - Wear parameters (Vertical, Horizontal and Angular Wear, Hollow, Difference of Diameters, Even/Uneven Wear),
 - Angular Profile Parameters,
 - Rim Width and Thickness,
 - Wheel Diameter,
 - Wheel Defects (Slides and Cavities),
 - Special Flange Parameters of the Tram Wheel and etc.;
- Setting of displayed Identification Parameters of the Wheelset. I.e., you can select only required parameters (number, series, operator, mileage, and etc.) for displaying on the screen;
- Simple Calibration Procedure: it performs automatically by clicking one button;
- The possibility to compare several Saved Profiles;

IKP-5 SOFTWARE

- The possibility to align Measured Profile manually (by buttons) relative to the reference with saving;
- Possibility to save several Bluetooth-devices in the PDA memory and then to select the required one from the list. I.e. You save addresses of several IKP and after that you need only to select the required one from the list without a necessity of searching procedure (the same is for IMR and IDK);
- Possibility to connect PDA to PC as an External Storage Device (alternative of ActiveSync).



WHEEL DIAMETER MEASUREMENT GAUGE

IDK Series

Electronic gauge is designed for measuring wheel rolling circle diameter. Measurements are made directly on rolling stock without wheel set roll-out. The measurement of the diameter is performed according to the "three points" technique, without the complete wheel coverage.

The gauge contains numeric display to show the value of the wheel diameter. IDK-BT gauge contains Bluetooth interface for transfer results into wheel-set wear database management system.

| Parameter | Value |
|---|---|
| Measurement range, mm | 4001400 or on request |
| Measurement error, mm | ±0.2 |
| Indication discreteness | 0.1mm, 0.01mm * or 0.01 inch ** |
| Position of measurement, S, mm | On request |
| Distance between axes of ball bearings (base), mm and diameters measurement range, mm | 122±0.5 (400750 mm) or 200±0.5 (400950 mm) or 250±0.5 (6001400 mm) or 300±0.5 (7201400 mm) |
| Display | build-in, LED |
| Operating temperature, °C | -15+55 |
| Power supply | rechargeable battery 2 x AAA 1.2V |
| Weigh, kg | 0.5 |
| The number of measurements that can be taken before battery recharge is not less than | 1000 |



SPECIAL MODELS OF IKP-5 AND IDK FOR TRAMWAY WHEELS

Special models of IKP-5 and IDK are designed especially for measurement of wheels with restricted space for device placement (tramway wheels):

- Laser Wheel Profile Gauge model IKP-5-short (Fig. A) with a shortened handle,
- Laser Wheel Profile Gauge model IKP-5-Super short (Fig. B) version for Ansaldo Breda low floor trams,
- Wheel Diameter Measurement Gauge model IDK-compact (Fig. C) with the measurement base (distance between ball supports) of the gauge 122 mm and diameter measurement range 400...750 mm.



LASER PROFILOMETER FOR RAILROAD RAILS AND SWITCHERS



The device consists of frame for device placement on the rails and laser measurement head placed with possibility of linear translation. The measurements are carried out automatically. The measurement result is rails transfer profile.

| Parameter | Value |
|-----------------------|-------|
| Measurement range, mm | 600 |
| Measurement error, mm | ±0.1 |

BACK-TO-BACK DISTANCE MEASURING GAUGES

IMR and IMR-L Series

Electronic gauge is designed for measuring back-to-back distance of railway, metro and tram wheels in the course of checkup, examination, repair and formation of wheel sets. The method of measurement is based on direct measurement the distance by contactless laser sensor. Measurements are made directly on rolling stock without wheel set roll-out.

IMR SERIES





| Parameter | Value | |
|---------------------------|------------------------------------|--|
| Measurement range, mm | L±25 (L – nominal distance) | |
| Measurement error, mm | ±0.1 | |
| Indication discreteness | 0.1mm, or 0.01 inch ** | |
| Display | build-in, LED | |
| Operating temperature, °C | -15+50 | |
| Weigh, kg | 1 | |
| Dimensions, mm | D+137x30x124 | |
| Power supply | rechargeable batteries 2xAAA, 1.2V | |





| Parameter | Value | |
|---------------------------|---|--|
| Measurement range, mm | 13601440 or on request (nominal distance ± 15mm) | |
| Measurement error, mm | ±0.3 | |
| Indication discreteness | 0.1mm, 0.01mm * or 0.01 inch | |
| Display | build-in, LED | |
| Operating temperature, °C | -15+50 | |
| Weigh, kg | 0.85 | |
| Dimensions, mm | 234.2x87.7x32 | |
| Power supply | rechargeable batteries 4 x AA 1.2V | |
| Connection to PC | Bluetooth | |

DISK BRAKES PROFILE GAUGE

IKD Series

Profilometer uses non-contact method of registration with a laser sensor and a scanning device.

MAIN FUNCTIONALITY

- obtaining data on the parameters of railway wheel disk brakes working surface;
- full profile scanning and analysis of the working surface of disk brakes;
- visualization of combined graphic images of the actual and new profiles of the wheel brake disks;
- support of the electronic database of profiles.

Profilometer for measuring parameters of the disc brakes installed on the wheel.

Profilometer with a bracket for measuring parameters of the disk brakes installed on the wheelset axle.



| Parameter | Value | |
|---|--|--|
| Measurement range, mm | 30 | |
| Profile measurement range, mm | 150 | |
| Measurement error | ± 0.03 | |
| Discreteness of indication, mm | 0.01 | |
| Discreteness of the profile formation, not worse than, mm | 0.1 | |
| Power supply, laser module | 3.7 Li-ion rechargeable battery 6800 mAh | |
| Power supply, PDA | 3.7 Li-polymer battery 3300 mAh | |
| The number of measurements that can be taken before battery recharge is not less than | 1000 | |
| PDA memory capacity | 100 000 measurements | |
| Interface between laser scanning module and PDA | Bluetooth | |
| Working temperature range, °C | -15+35 | |
| Enclosure rating | IP42 | |

RAIL PROFILE MEASUREMENT GAUGE

PRP Series

Portable laser rail profilometer (PRP) is designed for non-contact registration of cross-section of the railhead acting face.

The profilometer uses non-contact method of registration with a laser sensor and a scanning device.

MAIN FUNCTIONALITY

- obtaining the information on the cross-section profile of the working railhead surface;
- full profile scanning and analyze of the railhead acting face;
- visualization of the combined graphical images of actual and new crosssection.

| Parameter | Value | |
|---|-----------------------------------|--|
| Railhead vertical wear, mm | -15.0+20.0 | |
| Lateral railhead wear, mm | -15.0+20.0 | |
| Redused railhead wear, mm | Up to 20.0 | |
| Scanning angle inside the rail track, degrees | 108 | |
| Scanning angle outside the rail track, degrees | 108 | |
| Measurement error, not more than, mm | ±0.03 | |
| Scanning time, sec | 10-12 | |
| Digital readout device (PDA) dimensions, mm | 112.5x95.5x22.7 | |
| Laser module dimensions, mm | 293x230x230 | |
| Power supply, laser module | 3.7V, Li-ion battery, 6800mAh | |
| Power supply, PDA | 3.7V, Li-polymer battery, 3300mAh | |
| The number of measurements that can be taken before battery recharge is not less than | 500 | |
| PDA memory capacity, no less | 100 000 measurements | |
| Interface to PC | Bluetooth | |

AUTOMATIC REAL-TIME SYSTEM FOR MEASUREMENT OF WHEELSETS GEOMETRICAL PARAMETERS

3DWheel Series

The system is intended for contactless automatic real-time measurement of geometrical parameters of railway vehicles (locomotives, railcars, subway, trams) and uses combination of 2D laser scanners mounted wayside in the track area and calibrated into one common coordinate system.

Measurement cycle starts when an inductive sensor detects a wheel.

While the wheel passes through the system of synchronized 2D laser scanners its profile is taken at many sections.

All measurement readings for all the wheels are sent through Ethernet to control computer for profiles reconstruction and dimensions calculations.

Finally, all the data are collected in the host depot computer in wheel sets wear database.









| | | Scanners inside |
|---------------|----------------|-----------------|
| | | Protective body |
| | | |
| 00 | | |
| 80 | | |
| | II II SD Wheel | |
| | | |
| Mounting plan | e | |

| Measurement error | | | |
|---|--|---|--|
| The following parameters need to be measured with | Maximum error. Train speed is up to 60 km/h | Maximum error. Train speed is up to 120 km/h | |
| Wheel diameter | ± 1.0 | ± 2.0 | |
| Flange height | ± 0.5 | ± 0.75 | |
| Flange width (thickness) | ± 0.5 | ± 0.75 | |
| Flange slope | ± 0.5 | ± 0.75 | |
| Rim thickness | ± 0.5 | ± 0.75 | |
| Wheel width | ± 0.5 | ± 0.75 | |
| Back-to-Back distance | ± 0.5 | ± 1.5 | |

DISTRIBUTORS

AUSTRALIA

Applied Measurement Australia Pty Ltd

RAILWAY INSTRUMENTS ONLY Thornton Plaza, Unit 5,

27 Thornton Crescent, Mitcham VIC 3132, Australia Tel: +61 39874 5777 Fax: +61 39874 5888 sales@appliedmeasurement.com.au www.appliedmeasurement.com.au

BULGARIA

ASCO RAIL sp. z o.o. EXCLUSIVE REPRESENTATIVE FOR RAILWAY EQUIPMENT ul. Wielowiejska 53, 44-120 Pyskowice, Poland Tel: +48 32 230 45 70 Fax: + 48 32 233 21 34 biuro@ascorail.pl/export@ascorail.pl www.ascorail.pl

CHINA

Beijing Gemston Mechanical & Electrical Equipment Co.,Ltd RAILWAY INSTRUMENTS ONLY

Room 613, Anfu Mansion, Fengtai District, Beijing, China Tel: +86 10 6765 0516 Fax: +86 10 6765 6966 Mobile: +86 137 1755 1423 dh0526@163.com www.baoft.cn

CHINA

Chongqing Wolf Industrial Technology Co.,Ltd Room 2307 / 2308,No. 19 J iangnan Avenue, Nan'an District, Chongqing, China Tel: 023-62832618 Fax: 023-62832113 www.wolf-hk.com info@wolf-hk.com

FINLAND

Teräspyörä-Steelwheel OY RAILWAY INSTRUMENTS ONLY Juvan teollisuuskatu 28 FI-02920 Espoo, Finland Tel: +358 400 422 900 Fax: +358 9 2511 5510 steelwheel@steelwheel.fi www.teraspyora.fi

GERMANY

ALTHEN GmbH Meß- und Sensortechnik Dieselstrasse 2 65779 Kelkheim, Germany Tel: +49 (0)6195 7 00 60 info@althen.de www.althensensors.com

BELGIUM

Althen Sensors & Controls BV Verrijn Stuartlaan 40, 2288 EL, Rijswijk, The Netherlands Tel: +31(0)70 392 4421 Tel: +31(0)61 396 7830 Tel: +31(0)64 323 8393 sales@althen.nl / info@althen.nl www.althensensors.com

CHILE

Verne SpA Apoquindo 2818, oficina 31, Las Condes, Santiago, Chile Tel: +56 2 228858633 info@verne.cl jsaavedra@verne.cl www.verne.cl

CHINA

Xi'an Win-Success Automation Technology Co.,Ltd. Room 3-1-1039, Iduhui Building, No.11 Tangyan South Road, High-Tech Zone, Xi'an, Shaanxi PRC, China Tel: +86 29 8110 6280 Fax: +86 29 8110 6285 Mob: +86 133 1927 1405 www.maxsensor.com info@maxsenor.com

CROATIA

ASCO RAIL sp. z o.o. EXCLUSIVE REPRESENTATIVE FOR RAILWAY EQUIPMENT ul. Wielowiejska 53, 44-120 Pyskowice, Poland Tel: +48 32 230 45 70 Fax: + 48 32 233 21 34 biuro@ascorail.pl/export@ascorail.pl

FRANCE

www.ascorail.pl

BLET Measurement Group 18 rue des Gaudines, 78100 Saint Germain en Laye, France Tel: +33(0)1 8088 5785 Fax: +33(0)1 8088 5793 technique@blet-mesure.fr www.blet-mesure.fr

HUNGARY

ASCO RAIL sp. z o.o. EXCLUSIVE REPRESENTATIVE FOR RAILWAY EQUIPMENT ul. Wielowiejska 53, 44-120 Pyskowice, Poland Tel: +48 32 230 45 70 Fax: + 48 32 233 21 34 biuro@ascorail.pl/export@ascorail.pl www.ascorail.pl

BRASIL

CAPI Controle e Automação Ltda Rua Itororó, 121, CEP 13466-240 Americana-SP, Brazil Tel: +55 19 36047068 Tel: +55 19 34681791 capi@capicontrole.com.br www.capicontrole.com.br

CHILE

MOL INGENIERIA LTDA EXCLUSIVE REPRESENTATIVE FOR RAILWAY EQUIPMENT República de Honduras # 11936, Las Condes, Santiago de Chile

Tel: +56 9 59200362 hconcha@molingenieria.com www.molingenieria.com

CHINA

Micron-Metrology co., Ltd. No.2, Kecheng Rd., Industrial Park District, Suzhou, Jiangsu Province., China Tel: +0512 6558 9760 Mob: +86 189 1806 9807 sales@micron-metrology.cn www.micron-metrology.cn

CZECH REPUBLIC ASCO RAIL sp. z o.o. EXCLUSIVE REPRESENTATIVE FOR RAILWAY EQUIPMENT

ul. Wielowiejska 53, 44-120 Pyskowice, Poland Tel: +48 32 230 45 70 Fax: + 48 32 233 21 34 biuro@ascorail.pl/export@ascorail.pl www.ascorail.pl

GERMANY

Disynet GmbH Breyeller Str. 2 41379, Brueggen, Germany Tel: +49 (2157) 8799 -0 Fax: +49 (2157) 8799 -22 disynet@sensoren.de www.sensoren.de

INDIA

Influx Big Data Solutions No:2, Krishvi, Ground Floor, Old Airport Road, Domlur, Bangalore - 560071. India Tel: +91 73 3774 8490 Tel: +91 94 4849 2380 milan@influxtechnology.com support_india@influxtechnology.com

BOSNIA AND HERZEGOVINA

ASCO RAIL sp. z o.o. EXCLUSIVE REPRESENTATIVE FOR RAILWAY EQUIPMENT

ul. Wielowiejska 53, 44-120 Pyskowice, Poland Tel: +48 32 230 45 70 Fax: +48 32 233 21 34 biuro@ascorail.pl/export@ascorail.pl www.ascorail.pl

CHINA

Beijing Haiwei Lutong Technology Co., Ltd. Yard 1, Tianxing Street, Fangshan District, Beijing, China Tel: +86-10-8366-1866 Fax: +86-10-8366-1866 www.haiwlt.com info@haiwlt.com

CHINA

Zhenshangyou Technologies Co.,Ltd. Rm 2205-2210, Zhongyou Hotel 1110 Nanshan Road, Nanshan District 518054 Shenzhen, China Tel: +86 755 26528100/8011/8012 Fax: +86 755 26528210/26435640 info@51sensors.com www.51sensors.com

DENMARK

BLConsult Ryssbält 294, 95 291 Kalix, Sweden Tel: +46 70663 1925 info@blconsult.se www.blconsult.se

GERMANY

Finger GmbH & Co. KG OPTICAL MICROMETERS ONLY Sapelloh 172, 31606 Warmsen, Germany Tel: +49 5767 96020 Fax: +49 5767 93004 finger@finger-kg.de www.finger-kg.de

INDIA

Paragon Instrumentation Engineers Pvt. Ltd. RAILWAY INSTRUMENTS ONLY 200,Station Road, Roorkee, 247 667, India Tel: +91 1332 27 2394 tanuj@paragoninstruments.com www.paragoninstruments.com

DISTRIBUTORS

INDONESIA

PT. DHAYA BASWARA SANIYASA Botanic Junction Blok H-9 NO. 7 Mega Kebon Jeruk, Joglo Jakarta, 11640, Indonesia Tel: +62 21 2932 5859 management@ptdbs.co.id

LATVIA, ESTONIA FoodLab OÜ Haabersti linnaosa, Astangu tn 52, 13519 Eesti, Tallinn, Estonia Tel: +372-56363110 foodlab.ee@gmail.com

NETHERLANDS

Althen Sensors & Controls BV Verrijn Stuartlaan 40, 2288 EL, Rijswijk, The Netherlands Tel: +31(0)70 392 4421 Tel: +31(0)61 396 7830 Tel: +31(0)64 323 8393 sales@althen.nl / info@althen.nl www.althensensors.com

POLAND ASCO RAIL sp. z o.o. EXCLUSIVE REPRESENTATIVE FOR

RAILWAY EQUIPMENT ul. Wielowiejska 53, 44-120 Pyskowice, Poland Tel: +48 32 230 45 70 Fax: + 48 32 233 21 34 biuro@ascorail.pl/export@ascorail.pl www.ascorail.pl

SLOVENIA

ASCO RAIL sp. z o.o. EXCLUSIVE REPRESENTATIVE FOR RAILWAY EQUIPMENT ul. Wielowiejska 53, 44-120 Pyskowice, Poland Tel: +48 32 230 45 70 Fax: + 48 32 233 21 34 biuro@ascorail.pl/export@ascorail.pl www.ascorail.pl

SWITZERLAND ID&T GmbH Arova halls, Winterthurerstrasse 702. CH-8247 Flurlingen. Switzerland Tel: +41 44 994 9232 Fax: +41 44 994 9234 info@idtlaser.com www.idtlaser.com

ISRAEL

Nisso Dekalo Import Export LTD 1 David Hamelech Street Herzlia 46661 Israel Tel: +972 9957 7888 Fax: +972 9956 8860 eli@fly-supply.net www.fly-supply.net www.aircraft-partsupply.com

LUXEMBOURG

Althen Sensors & Controls BV Verrijn Stuartlaan 40, 2288 EL, Rijswijk, The Netherlands Tel: +31(0)70 392 4421 Tel: +31(0)61 396 7830 Tel: +31(0)64 323 8393 sales@althen.nl / info@althen.nl www.althensensors.com

NORWAY Salitec AS

C.J. Hambros plass 2C, 0164 OSLO, Norway Tel.: +47 2389 1015 Fax: +47 9210 1005 mail@salitec.no www.salitec.no

PORTUGAL Campal Inovacoes Ferroviarias Lda. Lagoas Park, Edifício 7, 1° Piso Sul 2740-244 Porto Salvo, Oeiras, Portugal Tel: +351 21 584 4348 campal@campal.pt www.campal.pt

SOUTH KOREA PROSEN. CO., LTD M-1001, Songdo techno park IT center, 32, Songdogwahak-ro, Yeonsu-gu, Incheon, 21984, Republic of Korea Tel: +82 32 811 3457 Fax: +82 32 232 7458 trade@prosen.co.kr www.prosen.co.kr

SWEDEN BLConsult Ryssbält 294, 95 291 Kalix, Sweden Mobile: +46 70 663 1925 info@blconsult.se www.blconsult.se

ITALY

FAE s.r.l. Via Tertulliano, 41 20137 Milano, Italy Tel: +39 02 5518 7133 Fax: +39 02 5518 7399 fae@fae.it www.fae.it

MALAYSIA

OptoCom InstruVentures H-49-2, Jalan 5, Cosmoplex Industrial Park, Bandar Baru Salak Tinggi, Sepang, Malaysia Tel: +603 8706 6806 Fax: +603 8706 6809 optocom@tm.net.my www.optocom.com.my

NORWAY

BLConsult Ryssbält 294, 95 291 KALIX, Sweden Contactperson: Berndt Lundström Tel.: +46 70 663 1925 info@blconsult.se www.blconsult.se

SERBIA ASCO RAIL sp. z o.o. EXCLUSIVE REPRESENTATIVE FOR RAILWAY EQUIPMENT

ul. Wielowiejska 53, 44-120 Pyskowice, Poland Tel: +48 32 230 45 70 Fax: + 48 32 233 21 34 biuro@ascorail.pl/export@ascorail.pl www.ascorail.pl

SOUTH KOREA

BS Holdings Room B-201, Shinmyung Twintower 743-2, Choji-Dong, Danwon-Gu, Ansan 425856, Republic of Korea Tel: +82 31 411 5011 Fax: +82 31 411 5015 bsh5011@hanmail.net www.lasersolution.co.kr

SWEDEN, FINLAND

Kvalitest Industrial AB EXCEPT FOR RAILWAY INSTRUMENTS Ekbacksvägen 28, 16869 Bromma, Sweden Tel: +46 (0)76 525 5000 sales@kvalitest.com www.kvalitest.com www.kvalitest.com

JAPAN

Tokyo Instruments, Inc. 6-18-14 Nishikasai, Edogawa-ku, Tokyo, 134-0088 Japan Tel: +81 3 3686 4711 Fax: +81 3 3686 0831 f_kuribayashi@tokyoinst.co.jp www.tokyoinst.co.jp

MONTENEGRO

ASCO RAIL sp. z o.o. EXCLUSIVE REPRESENTATIVE FOR RAILWAY EQUIPMENT

ul. Wielowiejska 53, 44-120 Pyskowice, Poland Tel: +48 32 230 45 70 Fax: + 48 32 233 21 34 biuro@ascorail.pl/export@ascorail.pl www.ascorail.pl

PERU

Verne Perú S.A.C Las Codornices 104, Surquillo, Lima, Peru Tel/fax: +51 99243 6734 info@verne.com.pe www.verne.cl

SLOVAKIA ASCO RAIL sp. z o.o. EXCLUSIVE REPRESENTATIVE FOR RAILWAY EQUIPMENT

ul. Wielowiejska 53, 44-120 Pyskowice, Poland Tel: +48 32 230 45 70 Fax: +48 32 233 21 34 biuro@ascorail.pl/export@ascorail.pl www.ascorail.pl

SPAIN

IBERFLUID Instruments S.A. C/ Botanica, 122, 08908 L'Hospitalet de Llobregat, Barcelona, Spain Tel: +34 93 447 1065 Fax: +34 93 334 0524 myct@iberfluid.com www.iberfluid.com

THAILAND

Advantech Solution Co.,Ltd. 20/170 Motorway Rd., Kwang Pravet, Khet Pravet, Bangkok, Thailand 10250 Tel: +662 184 8705 Fax: +662 184 8708 sales@advantechsolution.com bundit.s@advantechsolution.com

DISTRIBUTORS

TURKEY

TEKMA Mühendislik A.Ş. Cevizli Mh. M. Kemal Cd., Hukukçular Towers, A-Blok, No: 66-A/39 Kartal – Istanbul Tel: +90 216 970 1318 Tel: +90 850 840 2334 info@tekma.eu www.tekma.eu

USA

Althen Sensors and Controls 2531 Bradley St., Oceanside CA 92056, USA Tel: (858) 633-3572 r.ream@althensensors.com

TURKEY

MAK Elektronik Malzeme Analiz ve Kalite Kontrol Cihazlari Dis Tic. Ltd. Sti.

Cenap Sahabettin Sokak, No:39, 34718 Kosuyolu – Kadikoy / Istanbul - Turkey Tel: +90 216 402 1034 Fax: +90 216 402 1035 ulastac@metalografi.net www.makelektronik.com.tr

USA, CANADA, MEXICO

Acuity Products of Schmitt Industries, Inc. 2765 NW Nicolai Street Portland, OR, 97210, USA Tel: +1 503 227 7908 sales@acuitylaser.com www.acuitylaser.com

UKRAINE

KODA Frunze st, 22 61002, Harkov, Ukraine Tel/Fax: +38 057714 2654 mail@koda.com.ua www.koda.com.ua

UNITED KINGDOM,

IRELAND Althen UK Northamptonshire, UK Tel: + 07823 921427 t.stoyles@althen.co.uk

USA, CANADA, MEXICO

International Electronic Machines Corporation RAILWAY INSTRUMENTS ONLY 850 River Street Troy, NY 12180, USA Tel: +1 518 268 1636 Fax: +1 518 268 1639 railway_marketing@iem.net www.iem.net



RIFTEK LLC

Email: info@riftek.com Site: www.riftek.com